

GO-GO[®]
ELITE TRAVELLER PLUS

THE QUICKEST WAY
TO TRAVEL.

GO-GO ELITE TRAVELLER[®] PLUS

The **Go-Go Elite Traveller[®] Plus** was designed to bring travel scooters to a greater range of people than ever before. An increase in length and width, and a weight capacity of 147 kg combine with wraparound delta tiller to allow both the larger individual and those with limited dexterity to experience the benefits of a travel specific mobility product for the first time. Feather-touch disassembly makes the Go-Go Elite Traveller Plus the easiest travel scooter to take along anywhere.



BUILT WITH PRIDE

Pride[®]
Mobility Products Ltd.



(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.com

Go-Go Elite Traveller® Plus	3-wheel	4-wheel
Weight capacity:	147 kg (23 Stone)	147 kg (23 Stone)
Maximum speed²:	Up to 6 km/h (4 mph)	Up to 6 km/h (4 mph)
Ground clearance¹:	7.5 cm (3") at midframe	7.5 cm (3") at midframe
Turning radius¹:	86 cm (34")	116 cm (45.75")
Overall length¹:	101.5 cm (40")	102 cm (40.25")
Overall width¹:	54 cm (21.125")	54 cm (21.125")
Tyres:		
Front:	5 cm x 20 cm (2" x 8") solid	5 cm x 20 cm (2" x 8") solid
Rear:	8 cm x 23 cm (3" x 9") solid	8 cm x 23 cm (3" x 9") solid
Anti-tips:	Rear	Rear
Transport weight:		
Total weight w/o battery pack:	38 kg (84 lbs.)	39.5 kg (87 lbs.)
Heaviest piece when disassembled:	14.74 kg (32.5 lbs.) (front section)	15.88 kg (35 lbs.) (front section)
Drive System:	24-volt DC motor, sealed mini-transaxle	
Dual Braking System:	Electronic, regenerative, and electromechanical	
Standard seating:	Foldable, compact, vinyl-covered molded plastic	
Battery Charger:	Off-board, 2-amp	
Battery Requirements³:	Two 12-volt, deep cycle (standard) Size: 2 x 18 AH (standard) Weight: 18 AH: 6.35 kg (14 lbs.) battery pack	

Standard Colours:



Blue



Red

2 sets of colours with every scooter!

¹ Due to manufacturing tolerances and continued product improvement, this specification is subject to a variance of +/- 3%.

² Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure.

³ Battery weight may vary based on manufacturer.

⁴ Range based on 4-wheel version.

Features

- Feather-touch disassembly with one hand
- Pride's exclusive black, low profile, non-scuffing tyres with new tri-spoke mags
- Delta tiller with wraparound handles
- 23 cm (9") rear wheels
- 147 kg (23 Stone) weight capacity
- Auto-connecting front to rear cable
- Includes 2 sets of easily changeable coloured panels - Red and Blue
- Front frame-mounted seat post offers maximum stability
- All new frame design easily disassembles into 5 super lightweight pieces for convenient transport and storage
- Modular design for easy serviceability
- Microprocessor-based controller offers optimal power management and added safety features
- Front tiller-mounted basket
- Removable footboard basket for additional storage (4-wheel version only)
- Convenient off-board dual voltage charger can charge battery pack on-board or off-board

Options

- Cup holder



Feather-touch disassembly



The information contained herein is correct at the time of publication; due to the manufacturers commitment to constant improvement and development, they reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.

32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL
(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.com

Pride
Mobility Products Ltd.